University of Applied Sciences and Arts of Southern Switzerland
Department of Environment Constructions and Design
Institute of Applied Sustainability to the Built Environment

SUPSI

Swiss BiPV Competence Centre

Datenblatt

Fassadenelementen

M125-32/P110-32 GEG LK

Produkt	**M125-32/P110-32 GEG LK**
Hersteller / CH Anbieter	**Solarwatt**
Adresse	**Solarwatt AG** **Maria-Reiche-Straße 8** **D-01109 Dresden Germany**
Kontakt	**Tel: +49 351 88 95 116** **Fax: +49 351 88 95 111** **Mail : info@solarwatt.de** **Web: www.solarwatt.de** **www.langleglas.com**

Produkt Details

Die Kombination der Module von Solarwatt (M115-50 GEG opak LK / P110-32 GEG opak LK) mit dem Befestigungssystem "Al-Wall" der Firma "Längle Glas", ein System für das Fassadendesign aus Standardkomponenten, kann für den Zusammenbau einer Länge von bis zu 20m verwendet werden (entsprechend der Vorschriften des jeweiligen Landes). Die Aluminiumprofile sind in verschiedenen Farben nach RAL-Farbkarten erhältlich. Dadurch wird eine bessere optische Integration gewährleistet.

Technologie:	**Monokristalline, multikristalline**
Leistung [W]:	**110-124**
Abmessungen [mm] L, b, d:	**1490 x 755 x 12**
Spezifische Leistung [W/m^2]:	**98.2-110.7**
Preis [CHF/m^2]:	**n.d.**
Modul Gewicht [Kg]:	**33**
Spezifisches Gewicht [Kg/m^2]:	**30**
Min. Neigung:	**n.d.**
Maßarbeit:	**Abmessungen, Farbe**
Zertifizierungen:	**IEC61215, IEC61730**

Produkt Einzelheiten