

## SUPSI

Swiss BiPV Competence Centre

### Detail sheet

---

## Facade elements

### M125-32/P110-32 GEG LK



<b>Product</b>	<b>M125-32/P110-32 GEG LK</b>
<b>Producer / CH supplier</b>	<b>Solarwatt</b>
<b>Address</b>	<b>Solarwatt AG Maria-Reiche-Straße 8 D-01109 Dresden Germany</b>
<b>Contact</b>	<b>Tel: +49 351 88 95 116 Fax: +49 351 88 95 111 Mail : <a href="mailto:info@solarwatt.de">info@solarwatt.de</a> Web: <a href="http://www.solarwatt.de">www.solarwatt.de</a> <a href="http://www.langleglas.com">www.langleglas.com</a></b>

### Product specifics

The combination of the modules Solarwatt (M115-50 GEG opaque LK / P110-32 GEG opaque LK) with the Al-Wall fastening system of the company Längle Glas is a system for the standard components façade design. Can be used for building up to 20m (according to country regulations). Aluminium profiles can be coloured according to RAL colour chart. This would allow a better visual integration.

<b>Technology:</b>	<b>Monocrystalline, multicrystalline</b>
<b>Power [W]:</b>	<b>110-124</b>
<b>Size [mm] L, w, t:</b>	<b>1490 x 755 x 12</b>
<b>Specific power [W/m<sup>2</sup>]:</b>	<b>98.2-110.7</b>
<b>Price [CHF/m<sup>2</sup>]:</b>	<b>n.d.</b>
<b>Module weight [Kg]:</b>	<b>33</b>
<b>Specific weight [Kg/m<sup>2</sup>]:</b>	<b>30</b>
<b>Min. tilt:</b>	<b>n.d.</b>
<b>Custom made:</b>	<b>Dimensions, color</b>
<b>Certifications:</b>	<b>IEC61215, IEC61730</b>

## Product details

