University of Applied Sciences and Arts of Southern Switzerland
Department of Environment Constructions and Design
Institute of Applied Sustainability to the Built Environment

SUPSI

Swiss BiPV Competence Centre

Datenblatt

Semitransparente Elemente für Glas

Schüco-Prosol



Produkt	**Schüco-Prosol**
Hersteller / CH Anbieter	**Schüco**
Adresse	**Jansen AG** **Industriestrasse 34** **CH- 9463 Oberriet**
Kontakt	**Tel: +41 71 763 95 23** **Fax: +41 71 761 27 38** **Mail : solar@jansen.com** **Web: www.jansen.com** **www.schueco.eu**

Produkt Details

Bei der Wahl der hochwertigen Gläser stehen unterschiedlichste Größen, Formate und Ausführungen zur Verfügung: von der einfachen Glas / Tedlar-Kombination bis zu Varianten mit Isolier-, Schallschutz- oder Sicherheitsgläsern.
Für PV-Füllungselemente mit Isolierglas können Ausführungen mit hervorragenden Ug-Werten anhand der Scheibenzwischenräume gewählt werden. Die g-Werte werden über die Zellbelegung definiert.

Technologie:	**Monokristalline, Multikristalline, Dünnfilm (a-Si)**
Leistung [W]:	**Hängt von der Auswahl des Moduls ab**
Abmessungen [mm] L, b, d:	**500-3000 x 500-2000 (Kurven sind möglich)**
Spezifische Leistung [W/m^2]:	**Hängt von der Auswahl des Moduls ab**
Preis [CHF/m^2]:	**n.d.**
Modul Gewicht [Kg]:	**Hängt von der Auswahl des Moduls ab**
Spezifisches Gewicht [Kg/m^2]:	**Hängt von der Auswahl des Moduls ab**
Min. Neigung:	**n.d.**
Maßarbeit:	**Abmessungen, Farbe (Rahmen), Form (Kurven)**
Zertifizierungen:	**IEC 61215, IEC 61646, IEC 61730**

Produkt Einzelheiten





