

SUPSI

Swiss BiPV Competence Centre

Detail sheet

Semi-transparent elements for glass

Schüco-Prosol



Product	Schüco-Prosol
Producer / CH supplier	Schüco
Address	Jansen AG Industriestrasse 34 CH- 9463 Oberriet
Contact	Tel: +41 71 763 95 23 Fax: +41 71 761 27 38 Mail : solar@jansen.com Web: www.jansen.com www.schueco.eu

Product specifics

This high quality glazing product is available in a wide choice of sizes, formats and finishes: from simple glass/Tedlar combinations to designs with double glazing, sound insulation or safety glass. For PV infill units with insulating glass, PV modules with excellent U_g values may be used, values achieved by the gaps between the panes. G values are defined according to the cell configuration.

Technology:	Monocrystalline, multicrystalline, thin film (a-Si)
Power [W]:	Depends on the choice of the module
Size [mm] L, w, t:	500-3000 x 500-2000 (curves are possible)
Specific power [W/m^2]:	Depends on the choice of the module
Price [CHF/m^2]:	n.d.
Module weight [Kg]:	Depends on the choice of the module
Specific weight [Kg/m^2]:	Depends on the choice of the module
Min. tilt:	n.d.
Custom made:	Dimensions, color (frame)
Certifications:	IEC 61215, IEC 61646, IEC 61730

Product details

